



Intumex® AB - Fire Stopping Coating

General

Intumex® AB is a waterbased endothermic coating. Good workability allows fast and clean installation of coated batts within openings.

Area of Application

Intumex® AB is a fire stopping coating for services in walls and floors. It is designed for use with cables, combustible and non-combustible pipes and joints without movement to seal against the spread of smoke and fire.

System Advantage / Customer Benefit

- ⇒ Non-expanding fire stopping coating
- ⇒ The coating remains flexible once dried

Technical Data

	Intumex® AB-L	Intumex® AB-M
Colour	white	white
Viscosity	60 - 100 Pa.s	320 - 440 Pa.s
Solids content	approx. 78 %	approx. 78 %
Density	approx. 1.50 g/cm ³	approx. 1.50 g/cm ³
pH-Value	7.5	7.5
Reaction to fire	B1 slowly combustible	B1 slowly combustible
Environmental compatibility	solvent-free, low odor, environment friendly	solvent-free, low odor, environment friendly



Certificate / Approval

- ⇒ EN 1366-3 (cable/cable bundles, pipes), EN 13501-2/classification reports

Packaging

- ⇒ 12.5 kg plastic buckets – 550 kg/pallet
- ⇒ 310 ml cartridges upon request
- Subject to change!

Storage Requirements

- ⇒ Store in cool and dry conditions
- ⇒ Protect from heat and frost
- ⇒ Shelf life of original sealed containers at least 12 months
- ⇒ Once opened, containers should be finished swiftly

Safety Instructions

- ⇒ Keep out of reach of children
- ⇒ Avoid contact with food or beverages
- ⇒ Please refer to the safety data sheet for additional advice