


**Intumex® AX** Electrical Switchbox Intumescent  
Fire stopping intumescent for electrical switchbox insulation.

# Fire *stopping*





# Intumex® AX - Electrical Switchbox Intumescent



## General

Intumex® AX is an intumescent material designed to compensate the breach in fire performance of fire resistant drywalls punctured by recessed electrical boxes. It is easily fitted into electrical boxes with no special tools or skill required.

## Area of Application

Recessed fitted single or double gang electrical boxes in fire resistant drywalls.

## System Advantage / Customer Benefit

- ⇒ Easy to install
- ⇒ Maintenance free
- ⇒ Cost effective

## Technical Data

Colour	Dark Grey
Dimension	70mm x 70mm
Thickness	8mm
Density	Nominal 900 kg/m <sup>3</sup>
Expansion rate	Nominal 1:12
Expansion temperature	Nominal 190°C



Before fire



After 120 minutes fire test

## Test Certificate / Approval

- ⇒ BS 476 Part 20

## Packaging

- ⇒ 84 pieces in a sheet

## Storage Requirements

- ⇒ Store in cool and dry conditions
- ⇒ Protect from heat and frost

## Safety Instructions

- ⇒ Keep out of reach of children
- ⇒ Avoid contact with food and beverages
- ⇒ For further details, please refer to our MSDS

## Installation



Step 1: Fix Intumex® AX into electrical box



Step 2: Connect the electrical cables



Step 3: Fix the cover in place

### Intumex Asia Pacific

#### MALAYSIA

Unit 19-02-01, Level 2, PNB Damansara  
 No.19 Lorong Dungun, Damansara Heights  
 50490 Kuala Lumpur  
 Tel: +60 (3) 2095 5111  
 Fax: +60 (3) 2095 6111

#### HONG KONG

Room 1011, C.C. Wu Building  
 302-308 Hennessy Road  
 Wanchai  
 Tel: +852 2895 0265  
 Fax: +852 2576 0216

#### AUSTRALIA

1 Scotland Road  
 Mile End South  
 SA 5031  
 Tel: +61 (8) 8352 6759  
 Fax: +61 (8) 8352 1014

#### SINGAPORE

10 Science Park Road, #03-14 The Alpha  
 Singapore Science Park II  
 Singapore 117684  
 Tel: +65 6292 7888  
 Fax: +65 6294 2576